


www.kebony.us | 833.795.8660 | info@kebony.us

# 1x6 Character 90 Degree Shiplap / #2216



Actual Dimensions: 21 x 148 mm Lengths: 3 m, 3.6 m, 4.2 m, 4.8 m

Moisture Content	8-14%
Knots/Pitch pockets	Contains only live knots
Cracks	Surface cracks may be visible
Cupping	Max. 2.5% of width
Crook	Max. 5mm/2 m (13/64")
Wane	May occur on the back.
Density	35.6 lb/ft3 570 kg/m3

Defects

There may be defects on the back side. These will not affect the technical quality of

the product.

**Stiffness (MOE)** 1,436,000 psi 9.9 GPa for 34mm

Characteristic Bending Strength (MOR)\*

3336 psi 23.0 MPa for 34mm \* Data provided do not have any safety factors applied.

Dimensional Stability (Swelling/Shrinkage)

Maximum Swelling (dry to wet, tangential direction): 6%

#### **CERTIFICATIONS**

FSC® CU-COC-813689 - www.fsc.org EPD: NEPD-407-288-EN - www.epd-norge.no





#### **EXAMPLE OF WEATHERING**



#### **DISCLAIMER**

Kebony products will change in appearance when exposed to rain and sun. Color changes and surface cracks will occur due to natural weathering. Kebony cannot be held liable for any such variations in colour and surface appearance. This will not influence durability and overall performance of the product.

Kebony is continuously working on product development. Information in this datasheet may be changed without further notice.



# BENEFITS/FEATURES

#### Maintenance

Kebony is a low maintenance wood that does not require any additional treatment beyond normal cleaning. Removal of dirt, sand and other particles is simply done with a brush and water.

### High resistance

Kebony is highly resistant to decay, fungi, insects and other wood-destroying microorganisms. That's why we are able to offer an outdoor lifetime warranty against rot for 30 years for all Kebony products in above-ground usage.

#### Safe & toxin-free

Kebony is not toxic to humans or the environment, neither in use nor at the end of it's life cycle. That's why Kebony is often selected for applications such as kindergarten as children will have direct contact with the wood. The wood does not splinter and contains no toxins or chemicals.

Waste from Kebony boards can be disposed of and recycled in the same manner as untreated wood. Kebony can be burnt like untreated wood, and will not release any other components than those released when burning untreated wood.

## **Eco-friendly**

Kebony wood has no harmful effects on the environment. Production of Kebony is based on a liquid extracted from bio-waste and our factory produces to the most environmentally friendly standards.

#### Sustainable resources

The raw materials for Kebony are acquired from commercially managed forests with large timber harvests. All our suppliers hold certificates guaranteeing the origin of their timber.

Many Kebony products are FSC®-certified. The Forest Stewardship Council® (FSC®) works to improve forest management worldwide, and through certification it creates an incentive for forest owners and managers to follow best social and environmental practices. FSC® provides a connection between the forest and the end user, ensuring that products with the FSC® label uphold principles and criteria that adhere to the highest social and environmental benefits and considerations.