

www.kebony.us | 833.795.8660 | info@kebony.us

1x6 Clear 90 Degree Shiplap / #K90XX514		
3∕4 ^u ↓	5 ¾"	Face: 5 ¼" Actual Dimensions: ¾" x 5 ¾" Lengths: 10', 12', 14', 16'
Quality & Appearance Upon Delivery		
Knots/Pitch Pockets	May be visible and are a natural occurrence in wood	Hardness (Janka) 1618 lb 7.2 kN
Cracks	Surface cracks and checks may be visible	Fire Rating Class B as per ASTM Designation E84-15a, "Standard Method of Test for Surface Burning Characteristics of Building Materials".
Wane	May occur on the back	
Moisture Content	4-8%	Dimensional Stability (Swelling/Shrinkage) Maximum Swelling (dry to wet, tangential direction): 4% NOTE There may be defects on the back side. These will not affect the technical quality of the product. The board is not reversible.
Cupping	Max. 2% of width	
Density	41.8 lb/ft3 670 kg/m3	
Crook	10′ 12′: Max. 10mm (²5′64″) 14′ 16′: Max. 13mm (³¾64″)	
CERTIFICATIONS FSC® SCS-COC-008513 - www.fsc.org EPD: NEPD-407-287-EN - www.epd-norge.no		
EXAMPLE OF WEATHERING		

DISCLAIMER

Kebony products will change in appearance when exposed to rain and sun. Color changes and surface cracks will occur due to natural weathering. Kebony cannot be held liable for any such variations in colour and surface appearance. This will not influence durability and overall performance of the product.

000

Kebony is continuously working on product development. Information in this datasheet may be changed without further notice.

Up to 5% of the delivered boards may be outside this specification and must be accepted.

BENEFITS/FEATURES

Maintenance

Kebony is a low maintenance wood that does not require any additional treatment beyond normal cleaning. Removal of dirt, sand and other particles is simply done with a brush and water.

High resistance

Kebony is highly resistant to decay, fungi, insects and other wood-destroying microorganisms. That's why we offer a 30-yr limited warranty against rot for residential use and a 25-yr limited warranty for commercial use. For more details, view US warranty info on www.kebony.us

Safe & toxin-free

Kebony is not toxic to humans or the environment, neither in use nor at the end of it's life cycle. That's why Kebony is often selected for applications such as kindergarten as children will have direct contact with the wood. The wood does not splinter and contains no toxins or chemicals.

Waste from Kebony boards can be disposed of and recycled in the same manner as untreated wood. Kebony can be burnt like untreated wood, and will not release any other components than those released when burning untreated wood.

Eco-friendly

Kebony wood has no harmful effects on the environment. Production of Kebony is based on a liquid extracted from bio-waste and our factory produces to the most environmentally friendly standards.

Sustainable resources

The raw materials for Kebony are acquired from commercially managed forests with large timber harvests. All our suppliers hold certificates guaranteeing the origin of their timber.

Many Kebony products are FSC®-certified. The Forest Stewardship Council® (FSC®) works to improve forest management worldwide, and through certification it creates an incentive for forest owners and managers to follow best social and environmental practices. FSC® provides a connection between the forest and the end user, ensuring that products with the FSC® label uphold principles and criteria that adhere to the highest social and environmental benefits and considerations.