

www.kebony.us | 833.795.8660 | info@kebony.us

| | 98 mm | Actual Dimensions: 21 x 98 mm* | |
|----------------------------------|--|--|--|
| 21 mm | | Lengths: 3.8 m, 4.4 m, 5.0 m | |
| <u>+</u> | | * Due to the Kebor of the profile can | y process the dimension vary +/- 3% |
| | Quality & Appear | ance Upon Deliv | very |
| Moisture Content | 8-14% | Defects | There may be defects on the |
| Knots/Pitch pockets | Contains only live knots | affect the technical of the product. | back side. These will not affect the technical quality |
| Cracks | Surface cracks may be visible | | |
| Cupping | Max. 2.5% of width | Dimensional Stability (Swelling/Shrinkage) Maximum Swelling (dry to wet tangential direction): 6% | |
| Crook | Max. 5 mm/2 m (13/64") | | |
| Wane | May occur on the back | | |
| Density 12% mc | 35.6 lb/ft3 570 kg/m3 | | |
| | CERTIFICATIONS FSC® SCS-COC-008513 – www EPD: NEPD-407-288-EN – www | | SC epd [®] |
| | EXAMPLE OF | WEATHERING | |
| | | | |
| | ud not he further machined or split as untrasted | haartwood will be averaged | Kabany Character products can be cross out to |
| ength. Exposed end grain after | uld not be further machined or split as untreated cross-cutting must be treated with a wood prese | rvative. | , , |
| e held liable for any such varia | tions in colour and surface appearance. This will | r changes and surface crack not influence durability and | s will occur due to natural weathering. Kebony cann overall performance of the product. |
| , | s may be outside this specification. | | |