

www.kebony.us | 833.795.8660 | info@kebony.us

1x6 Character 90 Degree Shiplap / #2216



Actual Dimensions: 21 x 148 mm* Lengths: 3.8 m, 4.4 m, 5.0 m

* Due to the Kebony process the dimension of the profile can vary +/- 3%

Quality & Appearance Upon Delivery

Moisture Content	8-14%	Defects	There may be defects on the back side. These will not affect the technical quality of the product. Boards are not reversible.
Knots/Pitch pockets	Contains only live knots		
Cracks	Surface cracks may be visible		
Cupping	Max. 2.5% of width	Dimensional Stability (Swelling/Shrinkage) Maximum Swelling (dry to wet, tangential direction): 6%	
Crook	Max. 5 mm/2 m (13/64")		
Wane	May occur on the back		rangermar arrection). 0%
Density 12% mc	35.6 lb/ft3 570 kg/m3		

CERTIFICATIONS

FSC® SCS-COC-008513 - www.fsc.org EPD: NEPD-407-288-EN - www.epd-norge.no





EXAMPLE OF WEATHERING



DISCLAIMER

Kebony Character products should not be further machined or split as untreated heartwood will be exposed. Kebony Character products can be cross-cut to length. Exposed end grain after cross-cutting must be treated with a wood preservative.

Kebony products will change in appearance when exposed to rain and sun. Color changes and surface cracks will occur due to natural weathering. Kebony cannot be held liable for any such variations in colour and surface appearance. This will not influence durability and overall performance of the product.

Up to 5% of the delivered boards may be outside this specification.

Kebony is continuously working on product development. Information in this datasheet may be changed without further notice.

Kebony Character products contain knots and untreated heartwood. The amount of heartwood will vary from board to board.